



DECLARATION OF PERFORMANCE

No. 35/1

1. **Birch Plywood Type FSF with the thickness < 9 mm (FSF < 9)**
2. Batch no.: see package.
3. For internal use in humid conditions (uncoated) and for external use (coated and with sealed edges) as non-structural components –
EN 13986 : 2004 (4.5, 4.6)
4. Manufacturer: **LLC “SVEZA Uralskiy”**
1a Moskovskaya str., Uralskiy, Nytva District, Perm Region
617005, RUSSIA
5. Non-applicable
6. System of assessment and verification of consistency of performance of the construction product as set out in Annex V: EN 13986:2004 System 4
7. Non-applicable
8. Non-applicable
9. Declared performance:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonized technical specification</i>
Bonding quality	Class 3	EN 636 : 2012
Formaldehyde release	Class E1	EN 636 : 2012, Table 3
Reaction to fire	Class F	EN 13501 : 2002


10. The performance of the product is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Uralskiy, February 13th, 2015




Matvey V. Vyatkin
Director of Branch „Uralskiy“
of JSC „SVEZA“



DECLARATION OF PERFORMANCE

No. 35/2

- Birch Plywood Type FSF with the thickness 9-35 mm (FSF 9-35)**
- Batch no.: see package.
- For internal use in humid conditions (uncoated) and for external use (coated and with sealed edges) as structural components –
EN 13986 : 2004 (4.2, 4.3)
- Manufacturer: **LLC “SVEZA Uralskiy”**
1a Moskovskaya str., Uralskiy, Nytva District, Perm Region
617005, RUSSIA
- Non-applicable
- System of assessment and verification of consistency of performance of the construction product as set out in Annex V: EN 13986:2004 System 2+
- The notified body:

- 1075 -

The Bremen Institute for Materials Testing (MPA Bremen)
Paul-Feller-Str. 1, 28199 Bremen, Germany

has performed the certification in accordance with EN 13986, System 2+ and issued the certificate of conformity of the factory production control:

1075-CPR-Z342-2/15

- Non-applicable
- Declared performance:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonized technical specification</i>
Bending strength	F40/30	EN 636 : 2012, Table 1
Modulus of elasticity	E70/30	EN 636 : 2012, Table 2
Bonding quality	Class 3	EN 636 : 2012, EN 314-2:1993
Formaldehyde release	E1	EN 636 : 2012, Table 3
Reaction to fire	D-s2, d0	EN 13986:2004, Table 8


- The performance of the product is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Uralskiy, February 13th, 2015




Matvey V. Vyatkin
Director of Branch „Uralskiy“
of JSC „SVEZA“